

Short information:

Milliamp Loop Diagnostic Calibrator 334Plus

Manufacturer: PIECAL

Calibrate Milliamp Instruments

- Source 0.00 to 24.00 mA & -25.0 to 125.0% of 4-20 mA
- Read 0.00 to 52.00 mA
- Read -99.99 to 99.99 V
- Simulate 2-Wire Transmitters, Power & Read Transmitters
- Menu Selectable 250 Ohm resistor for HART compatibility

Calibrate with Lab Accuracy

- Accurate to $\pm(0.02\%$ of Reading + 0.002 mA)

Easy-to-Read Backlit Display

Locate Loop Current Leakages

- Automatic indication of Loop Current and Leakage Current
- Measure ground current leakage from faulty wiring, flooded conduit and corrosion bridges
- Leakage typically appears as a *Zero Shift* and helps you decide if the transmitter needs calibration or if there is a problem in the loop wiring

Faster Calibrations

- Three output EZ-CHECK switch
- 2 speed EZ-DIAL
- Stepping & Ramping

Includes Rubber Boot & Test Leads

Optional Accessories

- AC Adaptor 120 V (020-0101); 240 V (020-0100)
- NiMh Batteries & Charger 120 VAC/12V DC (020-0103)

Price on request

Article-No.: PIE 334Plus